

FIBPOXY BITUTACK PRIMER

Bituminous Base Surface Penetrating Primer

Product # 114.122

Version no: 16.11.23

Data
Tech

PRODUCT DESCRIPTION: A cold applied solvent based bituminous solution designed to penetrate and seal porous surfaces specially formulated for corrosion protection.

AREAS OF APPLICATION

- Slate
- Concrete
- Asbestos cement
- Metals - mild steel, zinc, lead
- Lightweight concrete screeds

ADVANTAGE

- Helps in corrosion protection of substrate
- USE where vertical walls is exposed to sand filing
- Walls where exposure is to water bodies
- Resistant to rainfall within 20-30 minutes of its application

APPLICATION

SURFACE PREPARATION

Cement bound surfaces must be dry, firm, offer good traction, free from loose particles, dust, dirt and additionally free of oil, grease and other impurities which can adversely affect uniform adhesion. If considered necessary, the surface should be sand blasted, flame scaled, milled or ground. Iron and steel must be free of rust and scale and should be free from oil, dust, grease and other dirt particles. The best method of preparation is to flame scale or sandblast/Mechanically Treated.

MIXING

FIBPOXY BITUTACK PRIMER requires no pre-blending and should be used directly from the container but stir well before use.

APPLYING AND LAYING

The mixed material should be applied to the prepared surface using brush or spray. Ensure mix material is spread evenly. Do not re-BRUSH later. The work area should be protected during the installation process and during the initial curing time to ensure that no airborne debris can contaminate the surface.

CLEAN UP

- Clean all tools immediately after use with Fibrex Paint Remover. Do not allow material to harden.

TECHNICAL SPECIFICATIONS

Color	Black
Specific Gravity @ 30°C	1 – 1.2
Flash Point °C	>120°C
Viscosity	70-160 cps
Water Content in %	< 0.2
Coverage	
Note: It varies according to the porosity of the surface	
Metal Surface	6 m ² per ltr
Concrete Surface	4 m ² per ltr
Lightweight Concrete Screeds & Asbestos Cement	3.5 m ² per ltr
Dry time in Hours :	
1) Touch Dry	1 hour
2) Hard Dry	5 hours
Consistency	Brush-able
Service temperature	5 to 50°C

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

PACKAGING

Fibpoxy bitutack primer 20 ltr can.

STORAGE

Store the material at temperatures between + 10° C and + 35° C in originally sealed packages, the material can be stored for twelve months. But before opening the drums, be assured that the temperature of the materials has the ambient temperature to avoid condensation. Open containers of material should be used quickly to avoid moisture contamination.

PRECAUTIONS

During mixing and application the following precautions should be observed: ensure adequate ventilation and avoid contact of the material with the eyes, nasal passages, mouth and unprotected skin. Avoid contact with the hands by wearing protective gloves and using, if necessary, a suitable barrier cream. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice and after contact with the skin wash immediately with plenty of soap and water (do not use solvents). Prolonged contact with the skin should be avoided, especially where the user has an allergic reaction. Always wear gloves and eye/face protection as necessary.

FIBPOXY BITUTACK PRIMER

Bituminous Base Surface Penetrating Primer

Product # 114.122
Version no: 16.11.23

Tech Data

Observe personal hygiene, particularly washing the hands after work has been completed or at any interruption whilst work is in progress. Care should be taken when removing gloves to avoid contaminating the insides. In case of accidents seek medical advice.

DISPOSAL / SPILLAGE

Spillage of the product should be absorbed onto sand or other inert material and transferred to a suitable disposable vessel. Disposal of such spillage or empty packaging should be in accordance with local waste disposal authority regulations.

NOTE

The information supplied in this datasheet is based upon extensive experience and is given in good faith in order to help you. Our company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof.

HEALTH AND SAFETY

This material is intended to be used by trained professionals with proper equipment's. The following safety measures are recommended:

- Wear protective gloves, clothing, goggles, hearing protection for noise reduction and hard hats for falling debris.
- Do not eat, drink or smoke while in active contact with these materials.
- Avoid skin contact.
- Wash hands thoroughly with soap and cool water.
- Never wash the skin with a solvent.
- Anyone experiencing difficulty breathing when working with these materials or showing an allergic reaction should seek fresh air immediately and consult a physician if symptoms persist.

DISCLAIMER:

Fibrex Construction Chemicals products though are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Fibrex Construction Chemicals wishes to clarify that any advice, recommendation, specification or information is accurate and correct, though it cannot, at any time assume any liability either directly or indirectly arising from the use of its products. This is because it has no direct or constant control over where or how its products are applied, and whether or not in accordance with the advice specification, recommendation or information given by it.

FIBREX OTHER PRODUCTS – WE DO

