

PRODUCT DESCRIPTION: Ficool is a unique formulation have waterproofing properties and heat reflecting pigments to reflect solar energy, especially energy in the infrared spectrum. Product is based on exterior grade liquid rubber which ensures very high exterior performance. This significantly reduces heat transfer into indoor areas, which reduces average indoor temperatures by 5°C and reduces dewing to improve the coating's durability. When applied to the exterior of a building, Ficool reduces internal heat gain from walls and roofs to help keep the interior cool and reduce use of air conditioning. And, like any other Fibrex product, it is designed for easy application and results in a long-lasting and beautiful finish. A breathable, elastomeric waterborne topcoat, Ficool uses an advanced hybrid resin technology to ensure excellent anti-carbonation properties and crack-bridging ability. Thanks to the combined effect of heat reflecting pigments and glass microspheres with sol gel, Ficool increases the total solar reflection by more than 100 percent compared to conventional coatings. This significantly reduces the transfer of heat into indoor areas, which reduces average indoor temperatures by 5°C and cuts cooling time and cost. As a result, Ficool can reduce a building's energy consumption by 5 percent.

AREAS OF APPLICATION

- Stone Tiles
- Clay Bricks
- Concrete
- Plastered Walls & Roofs
- Metal Sheets

ADVANTAGE

- Unique thermal insulation properties.
- Proven energy-saving capabilities.
- Waterborne coating.
- Low maintenance and long life
- Excellent anti-carbonation and anti-fungal properties.
- Lower heat cycling stress.
- Outstanding UV resistance and weather stability.
- Beautiful finish
- Wide range of pastel and light colors.
- Can be applied with textured rollers.

APPLICATION METHODOLOGY

SURFACE PREPARATION

Cement bound surfaces must be dry, firm, offer good traction, free from loose particles, dust, dirt and additionally free of oil, grease and other impurities which can adversely affect uniform adhesion. If considered necessary, the surface should be sand blasted, flame scaled, milled or grinded. Iron and steel must be free of rust and scale and should be free from oil, dust and grease and other dirt particles. The best method of preparation is to flame scale or sandblast.

MIXING

FICOOL requires no pre-blending and should be used directly from the container but stir well before use.

APPLYING AND LAYING

Apply at a uniform coverage by brush or roller application. If roller applied, use a short napped, solvent resistant sleeve.

CLEAN UP

Clean all tools immediately after use with water. Do not allow material to harden. Any hardened material will need to be removed mechanically.

TECHNICAL SPECIFICATIONS

| | |
|--|--|
| Consistency/Color | Thick Liquid/White |
| Specific Gravity | 1.2±0.2 |
| Total Solid Content | 62.0 – 64.0 % |
| Application Temperature | 10°C to 40°C |
| Drying Time & Over coat time | 3.5 to 4 hours @30°C & 80% RH |
| Average Adhesion strength (ASTM D4541) | 1.75±0.2MPa @ 28days |
| Elongation at break (ASTM D412) | >400% @22°C & 55% RH |
| Tensile strength (ASTM D412) | 3.4MPa @22°C & 55% RH |
| SRI (ASTM E1980) | >112 |
| Color Retention (IS 8709) | Pass |
| QUV 1000 hours (ASTM G 151) | Pass |
| Crack Bridging (ASTM C1305) | Pass (Upto 3.1 mm) |
| Flammability | Non Flammable |
| Anti-carbonation (BS EN 1062-6:2002) CO2 Diffusion coefficient | 8.93 x 10-8 cm2s-1 |
| Flexibility ASTM D522 | Pass |
| Consumption for Roofs | Eversil Primer – 100 gms/sqm Ficool – 1.6kg/m ² /1mm(two to three coats) |
| Consumption for Walls & Metal Sheds | Eversil Primer– 100 gms/sqm Ficool – 1.6kg/m ² /1mm(two to three coats) |

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Do not apply Ficool on surfaces known to, or likely to, suffer from rising dampness, potential osmosis problems or having relative humidity greater than 75 %. Consult fibrex before using Ficool in those areas.
- Do not apply Ficool to asphalt, weak or infirm concrete, unmodified sand-cement screeds, PVC tiles or sheets, or substrates known to move substantially e.g. steel walkways.
- Do not apply Ficool over treated expansion joints.

Please contact FIBREX for installation of floor coating over

- Oil / Fat rigged floors
- Floors with moisture content over 4 %
- Floors with rising moisture problem
- Asphalt based floor (interior)
- Floors with a pull off strength less than 1.5 N / mm²

PACKAGING

FICOOL is packaged in 20Kg bucket.

STORAGE

Store the material at temperatures between + 10° C and + 45° C in originally sealed packages, the material can be stored for 12 months. Open containers of material should be used quickly to avoid moisture contamination.

PRECAUTIONS

During mixing and application the following precautions should be observed: ensure adequate ventilation and avoid contact of the material with the eyes, nasal passages, mouth and unprotected skin. Avoid contact with the hands by wearing protective gloves, if necessary use a suitable barrier cream. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice and after contact with the skin wash immediately with plenty of soap and water (do not use solvents). Prolonged contact with the skin should be avoided, especially where the user has an allergic reaction.

Always wear gloves and eye/face protection as necessary. Observe personal hygiene, particularly washing the hands after work has been completed or at any interruption whilst work is in progress. Care should be taken when removing gloves to avoid contaminating the insides. In case of accidents seek medical advice.

DISPOSAL / SPILLAGE

Spillage of any of the component products should be absorbed onto sand or other inert material and transferred to a suitable disposable vessel. Disposal of such spillage or empty packaging should be in accordance with local waste disposal authority regulations.

NOTE

The information supplied in this datasheet is based upon extensive experience and is given in good faith in order to help you. Our company policy is one of continuous Research and Development, we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products; however as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof.

HEALTH AND SAFETY

This material is intended to be used by trained professionals with proper equipment's. The following safety measures are recommended:

- Wear protective gloves, clothing, goggles, hearing protection for noise reduction and hard hats for falling debris.
- Do not eat, drink or smoke while in active contact with these materials.
- Avoid skin contact.
- Wash hands thoroughly with soap and cool water.
- Never wash the skin with a solvent.
- Anyone experiencing difficulty breathing when working with these materials or showing an allergic reaction should seek fresh air immediately and consult a physician if symptoms persist.

Tech Data

DISCLAIMER:

Fibrex Construction Chemicals pvt. ltd. products though are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Fibrex wishes to clarify that any advice, recommendation, specification or information is accurate and correct, though it cannot, at any time assume any liability either directly or indirectly arising from the use of its products. This is because it has no direct or constant control over where or how its products are applied, and whether or not in accordance with the advice specification, recommendation or information given by it.

FIBREX OTHER PRODUCTS – WE DO

